→						+
L	0	SPK	S	SPK	0	L
	<u>a</u>				<u>A</u>	
→	\bigcup	S	С		Θ	•
L	0				0	L
	A	SPK	С	SPK	F	
-	9				Θ	+
L			0		D	L

•	MJ255 Luminaire	VIDEO CONFERENCE			
L	Relocated wall washer	Application: Committee Group (9 people) Light Distribution: Uniformity = very good Facial vertical foot-candles: very good			
SPK	Speaker	Luminaires: 6 MJ255			
С	Existing down light	Lens: none Ceiling height: 10'			
S	Sprinkler	Suspension: $0 = lay-in grid$ Horizontal distance: $7-9'$			
D	HVAC vent	Tilt from vertical: fixed @ 45 degrees Throw distance: 8-10'			
F	Fire indicator	Total power consumption: 660 Watts			
		Strategy: Note that the existing wall washers were shifted			

2' down. It is recommended that the existing can type down lights be turned off during

video-conference operation.



© PL Systems, Inc. 10529 Olympic Drive, Ste. 102 Dallas, TX 75220 (214) 393-5998 fax (214) 393-5999

Title

VIDEO CONFERENCE ROOM

Dec 21.2010

LAD 3.2.24

scale .25" = 1